



① PREPARE    ② TREAT    ③ MAINTAIN

# DIAMOND OIL ACTIVE

The first 1K oil that works like a 2K



**ONE LAYER  
PROTECTION**

1x



12h

**DRY IN  
12 HOURS**



eco

**ISOCYANATE  
FREE**

# Our best oil ever

You want your wooden floor to look amazing for decades to come without spending too much time. So you get the best oil there is.

The existing 2K solutions may dry fast, but contain Isocyanate and may require additional maintenance and repair over time.

In Denmark, we kept on pushing for a cleaner and greener solution and, after years of research, we found a better way. Yes, we wanted a product that is fast and easy to use. But we also wanted it to be strong and safe, while limiting waste to an absolute minimum.

Oil is the perfect natural solution for finishing wood surfaces and we are delighted to announce that we succeeded in combining our top of the line oil with a brand new technology. To cut a long story short: we are convinced that we created the best wood oil ever. The technology is called Hyper Cross Linking, which means the oil molecules form billions of extra connections, intensifying its

protective powers. Think of it as a web inside the wood that protects against moisture, dirt, and wear.

This final product we decided to call 'Diamond Oil Active'.



Diamond Oil Active is available in a variety of colours and can be applied fast, covering many square meters at once. The treated surface dries quickly and can be walked upon within twelve hours. Within five days, the wood is completely water repellent.

# Why use Diamond Oil Active

- The 1K oil with the 2K performance
- Super strong because of Hyper Cross Linking
- Protects from within in one coat
- Available in multiple colours

## Easy to apply

- 1** Clean the floor with WOCA Intensive Wood Cleaner. Leave the floor to dry for at least 8 hours before applying the oil.
- 2** Apply the oil using a short-bristled paint roller (3-4 mm) in an even coat.
- 3** Leave the oil to penetrate for 10-15 min. If the oil soaks quickly into the wood, apply more oil.
- 4** Rub the oil into the wood until the floor appears saturated. Use a buffing machine with a white or beige pad.
- 5** Remove excess oil with dry, lint-free cotton cloths or pads until the surface no longer appears wet.

The floor is dry in 12 hours and water-resistant after 5 days.



MADE IN DENMARK

# Choose the best finish for your woodwork

MORE INFORMATION  
[www.wocadenmark.com](http://www.wocadenmark.com)

FOLLOW US ON SOCIAL MEDIA



406020UK 0418



MADE IN DENMARK